



Pressure Seals, Inc. 315 Nutmeg Road South, South Windsor, CT 06074

626 and 666 SERIES U-CUP GROOVE DIMENSIONS

PSI U-CUP SERIES	NOMINAL CROSS-SECTION	*GROOVE DEPTH \pm .003	GROOVE WIDTH WALL TO WALL \pm .005	MAX. PISTON CLEARANCE
626-0XX 626-0XX	1/16	.060	.070	.002
626-1 666-1	3/32	.090	.110	.002
626-2XX 666-2XX	1/8	.115	.135	.002
626-50XX 666-50XX	5/32	.155	.165	.0025
626-3XX 666-3XX	3/16	.187	.195	.0025
626-70XX 666-70XX	7/32	.210	.235	.0025
626-4XX 666-4XX	1/4	.240	.260	.0025
626-90XX 666-90XX	9/32	.270	.310	.0025
626-100XX 666-100XX	5/16	.305	.325	.003
626-11XX 666-11XX	11/32	.335	.360	.003
626-12XX 666-12XX	3/8	.365	.400	.003
626-13XX 666-13XX	13/32	.400	.440	.003
626-16XX 666-16XX	1/2	.484	.540	.003

***FOR PISTON GROOVE, TWICE THIS DIMENSION SHOULD BE SUBTRACTED FROM CYLINDER DIAMETER FOR GROOVE ROOT DIAMETER.**

***FOR HOUSING GROOVE, TWICE THIS DIMENSION SHOULD BE ADDED TO CYLINDER DIAMETER FOR GROOVE ROOT DIAMETER.**



Pressure Seals, Inc. 315 Nutmeg Road South, South Windsor, CT 06074

"U" CUPS



Pruva Cup



Regular Style
U-Cup
AN6226

